

# PURE 58/47 MANUAL



PURE Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PU58M-A-SV)

New look door (PU58M-NL-SV)

PURE Manual (with ventilation) - Forced convection - Sealed device

Steel door (PU58M-A-AV)

New look door (PU58M-NL-AV)

Kw	efficiency %	CO (mg/Nm <sup>3</sup> )	COG (mg/Nm <sup>3</sup> )	Dust (mg/Nm <sup>3</sup> )	NOX (mg/Nm <sup>3</sup> )	el_max (kw)	el_min (kw)	el_sb (kw)
8	77	1250	117	39	34	0,026	0,019	0,000

Options → External dimensions (mm) : 580 x 470 x 420

Flat frame PURE 58 - 3 sided - 40mm → 652 x 508

Flat frame PURE 58 - 4 sided - 40mm → 652 x 540,5

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 20mm → 590 x 480

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 55mm → 590 x 480

Speed controller with airstat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

## Included

Manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)  
Real view of fire (mm) - 432 x 284



# PURE 58/47 FULL AUTOMATIC



PURE Automatic (with ventilation) - Forced convection - Sealed device

Steel door (PU58A-A-AV)

New look door (PU58A-NL-AV)

Kw	efficiency %	CO (mg/Nm <sup>3</sup> )	COG (mg/Nm <sup>3</sup> )	Dust (mg/Nm <sup>3</sup> )	NOX (mg/Nm <sup>3</sup> )	el_max (kw)	el_min (kw)	el_sb (kw)
8	77	1250	117	39	34	0,026	0,019	0,000

Options → External dimensions (mm) : 580 x 470 x 420

Flat frame PURE 58 - 3 sided - 40mm → 652 x 508

Flat frame PURE 58 - 4 sided - 40mm → 652 x 540,5

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 20mm → 590 x 480

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 55mm → 590 x 480

Speed controller with airstat

Speed controller with thermostat ambient temperature

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit

Reserve door fitting

Black painted vermic. interior

## Included

Automatic thermostat - external air intake Ø 100 mm - baffle vermiculite - stop embers - 2 centrifugal fans - interior vermiculite - speed controller, airstat - filter(s) - 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - WITHOUT FINISHING FRAME (following your choice)

Real view of fire (mm) - 432 x 284

