

# PURE 70/70 MANUAL



PURE Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PU70M-A-SV)

New look door (PU70M-NL-SV)

PURE Manual (with ventilation) - Forced convection - Sealed device

Steel door (PU70M-A-AV)

New look door (PU70M-NL-AV)

| Kw | efficiency % | CO<br>(mg/Nm <sup>3</sup> ) | COG<br>(mg/Nm <sup>3</sup> ) | Dust<br>(mg/Nm <sup>3</sup> ) | NOX<br>(mg/Nm <sup>3</sup> ) | el_max<br>(kw) | el_min<br>(kw) | el_sb<br>(kw) |
|----|--------------|-----------------------------|------------------------------|-------------------------------|------------------------------|----------------|----------------|---------------|
| 10 | 78           | 1125                        | 96                           | 15                            | 90                           | 0,052          | 0,037          | 0,001         |

Options → External dimensions (mm) : 700 x 700 x 470

Flat frame PURE 70 - 3 sided - 40mm → 772 x 738,5

Flat frame PURE 70 - 4 sided - 40mm → 772 x 772

Frame PURE 70 - drawn steel - 4 sided - 10 mm - depth 20mm → 710 x 710

Frame PURE 70 - drawn steel - 4 sided - 10 mm - depth 55mm → 710 x 710

Speed controller with airstat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

## Included

Manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)  
Real view of fire (mm) - 532 x 514



