

PURE 53/47 COMPACT (PU53V3)



A

PURE Manual (without ventilation) - Ecological combustion - Sealed device

PU53V3-AC-SV-VE / PU53V3-AC-SV-DM / PU53V3-AC-SV-BN

Steel door

PU53V3-NL-SV-VE / PU53V3-NL-SV-DM / PU53V3-NL-SV-BN

New look door

kW	Rendement %	CO (mg/Nm ³)	COG (mg/Nm ³)	Poussière (mg/Nm ³)	NOX (mg/Nm ³)	eI_max (kw)	eI_min (kw)	eI_sb (kw)
5.8	76.9	1125	92	21	125	0	0	0

Options

Dimensions ext. (mm) : 530 x 470 x 340

Flat frame PURE 53 - 3 sided - 40mm

Flat frame PURE 53 - 4 sided - 40mm

Frame PURE 53 - drawn steel - 4 sided - 10 mm - depth 20mm

Frame PURE 53 - drawn steel - 4 sided - 10 mm - depth 55mm

Hot air tubes kit 125 Ø + Air stop kit

Reserve door fitting

Interior : vermiculite (VE) or black concrete (BN) or metal decoration (DM)

Smoke outlet : 45° or right

Caractéristiques

Manual combustion air regulation - external air intake Ø 100mm - baffle vermiculite + 2e chicane inox - stop embers - 2 warm air tubes Ø 125 mm - smoke outlet Ø 150 mm - color anthracite - WITHOUT FINISHING FRAME (following your choice) - concrete floor
Real view of fire (mm) - 397 x 323

