

# PURE 58/47 COMPACT (PU58V3)



A

PURE Manual (without ventilation) - Ecological combustion - Sealed device

PU58V3-AC-SV-VE / PU58V3-AC-SV-DM / PU58V3-AC-SV-BN Steel door

PU58V3-NL-SV-VE / PU58V3-NL-SV-DM / PU58V3-NL-SV-BN New look door

kW	Rendement %	CO (mg/Nm <sup>3</sup> )	COG (mg/Nm <sup>3</sup> )	Poussière (mg/Nm <sup>3</sup> )	NOX (mg/Nm <sup>3</sup> )	e <sub>l_max</sub> (kw)	e <sub>l_min</sub> (kw)	e <sub>l_sb</sub> (kw)
8	76.9	1125	92	21	125	0	0	0

## Options

Dimensions ext. (mm) : 580 x 470 x 370

Flat frame PURE 58 - 3 sided - 40mm

Flat frame PURE 58 - 4 sided - 40mm

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 20mm

Frame PURE 58 - drawn steel - 4 sided - 10 mm - depth 55mm

Hot air tubes kit 125 Ø + Air stop kit

Reserve door fitting

Interior : vermiculite (VE) or black concrete (BN) or metal decoration (DM)

Smoke outlet : 45° or right

## Caractéristiques

Manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite + 2e chicane inox - stop embers - interior vermiculite or black concrete or metal decoration - 2 warm air tubes Ø 125 mm - smoke outlet Ø 150 mm - color anthracite - WITHOUT FINISHING FRAME (following your choice) - concrete floor  
Real view of fire (mm) - 447 x 323

