

# PURE 58/47 MANUAL



Pure Manual - Ecological combustion - Sealed device

Steel door or New look - Without ventilation	Réf.	Ventil.	kW	
Pure 58/47 manual - Steel door - verm. - 58x47x42	PU58M.A.SV	without	8	A
Pure 58/47 manual - New look door - verm. - 58x47x42	PU58M.NL.SV	without	8	A

Real view of fire - L 432 mm - H 284 mm

#### Option

Interior vermiculite painted black

Reverse door fitting

Finishing frame in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	652 x 508
4-sided frame - 40 mm flat 3 mm	652 x 540,5
4-sided frame étiré 10 mm depth 20 mm	590 x 480
4-sided frame étiré 10 mm depth 55 mm	590 x 480

#### Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers  
45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT  
FINISHING FRAME: optional



# PURE 58/47 FULL AUTOMATIC



Pure Automatic - Forced convection - Ecological combustion - Sealed decive

Steel door or New look - With ventilation	Réf.	Ventil.	kW	
Pure 58/47 full auto - Steel door - verm. - 58x47x42	PU58A.A.AV	with	8	A
Pure 58/47 full auto - New look door - verm. - 58x47x42	PU58A.NLAV	with	8	A

Real view of fire - L 432 mm - H 284 mm

#### Option

Speed controller with remote control

Speed controller with thermostat

Interior vermiculite painted black

2 small folted tubes of hot air Ø 125 mm

Stop air (only in combination with hot air tubes(s))

Reverse door fitting


Finishing frame in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	652 x 508
4-sided frame - 40 mm flat 3 mm	652 x 540,5
4-sided frame étiré 10 mm depth 20 mm	590 x 480
4-sided frame étiré 10 mm depth 55 mm	590 x 480

#### Included

Steel/New look door - automatic thermostat - external air intake Ø 100 mm - baffle vermiculite - stop embers - 2 centrifugal fans - interior vermiculite - speed controller, airstat - filter(s) - 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - WITHOUT FINISHING FRAME: optional



# PURE 58/47 MANUAL



Pure Manual - Ecological combustion - Sealed device

Steel door or New look - With ventilation	Réf.	Ventil.	kW	
Pure 58/47 manual - Steel door - verm. - 100x51x47	PU58M.A.AV	with	8	A
Pure 58/47 manual - New look door - verm. - 100x51x47	PU58M.NL.AV	with	8	A

Real view of fire - L 432 mm - H 284 mm

#### Option

Speed controller with remote control

Speed controller with thermostat

Interior vermiculite painted black

2 small folded tubes of hot air Ø 125 mm

Stop air (only in combination with hot air tube(s))

Reserve door fitting

Finishing frame in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	652 x 508
4-sided frame - 40 mm flat 3 mm	652 x 540,5
4-sided frame étiré 10 mm depth 20 mm	590 x 480
4-sided frame étiré 10 mm depth 55 mm	590 x 480

#### Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers - 1 centrifugal fan - interior vermiculite - 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite filter - WITHOUT FINISHING FRAME: optional

