

# VENTIL-ART 16/9 (MD16-9-V3)



A

## Modul-Art - Ecological combustion - Sealed device

MD16-9v3-Ac-VR / MD16-9v3-Ac-BN / MD16-9v3-Ac-DM

Steel door

MDWB-16-9v3-Ac-VR / MDWB-16-9v3-Ac-BN / MDWB-16-9v3-Ac-DM

Steel door / woodbox

MD16-9v3-NL-VR / MD16-9v3-NL-BN / MD16-9v3-NL-DM

New look door

MDWB-16-9v3-NL-VR / MDWB-16-9v3-NL-BN / MDWB-16-9v3-NL-DM

New look door / woodbox

kW	efficiency %	CO (mg/Nm <sup>3</sup> )	COG (mg/Nm <sup>3</sup> )	Poussière (mg/Nm <sup>3</sup> )	NOX (mg/Nm <sup>3</sup> )	e <sub>l_max</sub> (kW)	e <sub>l_min</sub> (kW)	e <sub>l_sb</sub> (kW)
12	77	900	59	22	57	0,000	0,000	0,000

## Options

Finishing kit (air intake cover)

Modul-Art Suspension kit (wall distance: 6.3cm)

Mounting opposite door

## Caractéristiques

Manual adjustment - external air intake Ø 100 mm - baffle(s) - stop embers - natural convection - vermiculite interior - colour antracite - choice of male back or top smoke outlet

External dimensions (mm) : 1010 x 525 x 485

Real view of fire (mm) - 852 x 324



