

LODGE 70



Lodge - Ecological combustion - Sealed device

LIFT door	Réf.	Ventil.	kW	
Lodge 70 - New look door - verm. - 815x1549x490	LO70	without	9 - 12	A+

Real view of fire - L 559 mm- H 503 mm

Option

Kit ventilation 1 x 750 m³/h with speedcontroller and airstat

Kit ventilation 2 x 140 m³/ h with speedcontroller and airstat

Speed controller with remote control

Speed controller with thermostat (RT012)

Interior vermiculite painted black

Finishing frame in 1 piece	External dimensions
4-sided frame - étiré 4 mm depth 55 mm	665x676
4-sided frame - étiré 4 mm depth 100 mm	677x688
4-sided frame - folded for panel - depth 55mm	741x748
4-sided frame - étiré 10 mm depth 55 mm	665x676
4-sided frame - étiré 10 mm depth 100 mm	677x688

Included

New look door - manual combustion air regulation - external air intake Ø 125 mm - interior vermiculite - without ventilation
4 adjustable feet - lift door with side opening for cleaning the glass - double baffle - 2 modules for convection air connection
Ø 150 mm - stainless steel Ø 200 mm nozzle for smoke outlet - colour antracite - WITHOUT FINISHING FRAME: optional



