

# LODGE 77



## Lodge - Ecological combustion - Sealed device

LIFT door	Réf.	Ventil.	kW	
Lodge 70 - New look door - verm. - 885x1149x490	LO77	without	10 - 12	A+

Real view of fire - L 628 mm - 304 mm

## Option

Kit ventilation 1 x 750 m<sup>3</sup>/h with speedcontroller and airstat

Kit ventilation 2 x 140 m<sup>3</sup>/ h with speedcontroller and airstat

Speed controller with remote control

Speed controller with thermostat (RT012)

Interior vermiculite painted black

Finishing frame in 1 piece	External dimensions
4-sided frame - étiré 4 mm depth 55 mm	735x476
4-sided frame - étiré 4 mm depth 100 mm	747x488
4-sided frame - folded for panel - depth 55mm	807x548
4-sided frame - étiré 10 mm depth 55 mm	735x476
4-sided frame - étiré 10 mm depth 100 mm	747x488

## Included

New look door - manual combustion air regulation - external air intake Ø 125 mm - interior vermiculite - without ventilation  
4 adjustable feet - lift door with side opening for cleaning the glass - double baffle - 2 modules for convection air connection  
Ø 150 mm - stainless steel Ø 200 mm nozzle for smoke outlet - colour antracite - WITHOUT FINISHING FRAME: optional

