

PURE 16/9 MANUAL (PU16-9-v3)



PURE Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PU16-9M-A-SV)

New look door (PU16-9M-NL-SV)

PURE Manual (with ventilation) - Forced convection - Sealed device

Steel door (PU16-9M-A-AV)

New look door (PU16-9M-NL-AV)

Kw	efficiency %	CO (mg/Nm ³)	COG (mg/Nm ³)	Dust (mg/Nm ³)	NOX (mg/Nm ³)	el_max (kw)	el_min (kw)	el_sb (kw)
12	77	900	59	22	57	0,052	0,037	0,001

Options → External dimensions (mm) : 1000 x 510 x 470

Flat frame PURE 16-9 - 3 sided - 40mm → 1072 x 547,5

Flat frame PURE 16-9 - 4 sided - 40mm → 1072 x 581

Frame PURE 16-9 - drawn steel - 4 sided - 10 mm - depth 20mm → 1010 x 520

Frame PURE 16-9 - drawn steel - 4 sided - 10 mm - depth 55mm → 1010 x 520

Speed controller with airstat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

Included

Manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers 45° angled stainless steel nozzle for smoke outlet Ø 180 mm - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)

Real view of fire (mm) - 852 x 324



